## **Speed Screed ® ROLLER**





**Manufactured By:** 



Form To Finish®

Need to slide entire

Smaller drive shaft

tube to change

Need to slide entire

Smaller drive shaft

tube to change

## Features and Advantages

| Features and Advantages Form To Finish®   |   |  |   |
|---|---|--|---|
| FEATURES  | ADVANTAGES  | Competitor - Model   |   |
|   |   | Fleming-medium   | Allen Eng-150   |
| Power Unit /Controls  • Simple operator interface • Ergonomic layout • Streamlined, electronically contolled hydraulics • Dual joystick control • "Smart" expandable system | <ul> <li>Simple, easy, joystick controls which<br/>eliminate overwhelming system of hydraulic<br/>levers</li> <li>Reduction in number of valves and hydraulic<br/>components which reduces heat</li> <li>Easily upgradeable for remote control</li> </ul> | Confusing system of<br>levers and labels<br>Not available              | Confusing system of<br>levers and labels<br>Not available |
| <ul> <li>35hp Kohler Engine</li> <li>Working Load Compensation</li> <li>12 gal. fuel tank</li> </ul>  | <ul> <li>Intuitive engine automatically increases throttle<br/>when required reducing fuel consumption</li> <li>Eliminates need for choke and reduces chance of<br/>engine flooding</li> </ul>  | Poor Fuel Economy  | Poor Fuel Economy   |
| <ul><li>In-joystick steering control</li><li>Min/Max steering leg notification</li></ul>  | <ul> <li>Drive and steer machine with one hand</li> <li>Steering leg up/down indicator for saftey</li> </ul>  | Not available  | Not available   |
| <ul> <li>Frame Assembly</li> <li>Modular frame</li> <li>Fork pockets for lifting</li> <li>Removable operator platforms</li> </ul>   | <ul> <li>Quickly extend / shorten machine for varying tube lengths</li> <li>Standard fork pockets for quick/easy jobsite transport</li> <li>Easily remove operator platforms for clearance</li> </ul>   | Not available in<br>modular lengths<br>Not available<br>Requires tools | Not available<br>Requires tools                           |
| Tube Counters   |   |  |   |

• Remove just six bolts and roll tubes in and out

2" Solid drive shaft for longer life1" of infinite ajustment on front "Slinger" tube

of machine

## **Tube Couplers**

- Quick 3-bolt change
- Solid 2" shaft assembly
- 1" Front "Slinger" tube

